

# Stanislav Yudin

## 2,500 tons



<b>Owner</b>	PO Lukoil - Kaliningradmorneft/SHL
<b>Builder</b>	Wärtsilä
<b>Delivered</b>	1982 (upgrades in 1992 and 19996)

## Description

The Russian Ministry of Gas ordered the self-propelled crane vessel "Stanislav Yudin" from the Finnish Wärtsilä shipyard in 1982.

The crane fitted on the stern of the vessel was designed by GustoMSC and built by Kone Oy in Finland.

### Main dimensions

Vessel length	approx. 183 m
Vessel width	36 m
Vessel depth	13 m

The crane was originally designed with two 800 ton main hooks, which could be operated separately, a 400 ton auxiliary hook and a trolley with a 30 ton hook which could travel along the length of the box girder crane boom. To lift the maximum load of 1,600 tons, the two main hooks can be used independently allowing an angle with the vertical of up to 15° or they can be coupled together by a hoisting beam with a 1,600 ton hook.

As the vessel has an active ballast system and a minimum draught was required, the weight of the crane is minimized by omitting the counterweight and by using high tensile steel.

The crane moment is taken by the GustoMSC bogie and counter bogie system, which has already successfully been applied on a wide variety of vessels.

Since it came into operation with Seaway Heavy Lifting B.V., the main and auxiliary hoists were upgraded (in 1992) to 2,000 tons for the main hook and 500 tons for the auxiliary hook. Later on the main hoist winches were enlarged for increased wire rope storage capacity (for deep water hoisting applications).

In 1996 the Stanislav Yudin was again upgraded to a main hook load of 2,500 tons. The hoisting, travelling and derrick winches as well as the slewing gear are driven by DC motors with a total power of 4,300 kW.

### Classification

The design meets the rules of the USSR Register of Shipping in Leningrad

### The Netherlands

Karel Doormanweg 66, 3115 JD, Schiedam  
P.O. Box 687, 3100 AR Schiedam

Telephone +31 (0)10 232 0800  
Telefax +31 (0)10 232 0801

[www.GustoMSC.com](http://www.GustoMSC.com)



## Design criteria

Load in metric tons	Speed in m/min
1 x 2,500	3
1 x 500	6
1 x 30	30

- Travelling speed trolley with 30 ton load up to 30 m/min
- Slewing speed at full load 0.3 rpm
- Boom hoist time with full load from horizontal position to min. outreach of 23 m approx. 40 min
- Boom hoist time with no load from horizontal position to min. outreach of 23 m approx. 20 min

- Static heel: 3 degrees for loads between 2,000-2,500 metric tons
- Static heel: 5 degrees for loads below 2,000 metric tons (Static heel is defined as the angle between the symmetric plane of the crane and the vertical plane.)
- Static loading in plane of the boom: 7°
- Static loading perpendicular to plane of the boom: 5°
- Wind load 400 N/m<sup>2</sup>
- Environmental loads simultaneous for lifts up to 2,500 ton fully revolving

Data presented in this product sheet is for information only. Unit specific specifications as provided by the Owner shall prevail.

